

# ROLINE 19-inch Network Cabinet Pro 47 U, 600x1000 WxD glass door grey

|                           |               |
|---------------------------|---------------|
| <b>Product No.</b>        | 26.21.0067    |
| <b>Manufacturer</b>       | ROLINE        |
| <b>Manufacturer No.</b>   | 26.21.0067    |
| <b>EAN (single piece)</b> | 7630049600683 |



## ROLINE 19 inch network cabinet Pro 47 U 600x1000 WxD glass door grey

The network cabinets in the ROLINE Pro series have been developed to enable particularly convenient and flexible network cabling. With brush inlets in the roof and base area (from 26U and 800 mm cabinet width), a slide-on inlet in the base chassis with foam rubber seal and brush strips above and below the rear door (from 26U), they offer a wide range of possible uses for various application scenarios. Vertical cable ducts with cover, installed next to the profile rails (from 800 mm enclosure width), complete the design. A stepped, removable cover with ventilation slots improves air circulation and allows easy installation of a fan module. Two pairs of galvanised 19" profile rails are installed inside, which can be read in both directions and are adjustable in depth. They are also connected to additional depth struts in the enclosure. Each cabinet consists of a robust steel construction with a material thickness of up to 1.5 mm sheet steel.

The colouring is carried out using electrostatic powder coating in the standard colours grey (RAL 7035) and black (RAL 9005). Modular removable side panels and doors improve accessibility. It is possible to change the door hinge. The cabinets can also be completely dismantled if required.

### Technical specifications

|               |                   |
|---------------|-------------------|
| Manufacturer  | ROLINE            |
| Product group | 19"/-10"-Cabinet  |
| Product type  | 19"-Floor cabinet |

|                              |  |
|------------------------------|--|
| Colour                       | grey   |
| Scope of delivery            | 19-inch network enclosure Pro 47 U, earthing cable set, installation kit for profile half cylinder, 2x spanners, installation set (screws, cage nuts, washers), instructions |
| Type of profile rail         | L-shaped   |
| Modular spacing              | 482.6 mm (19 inch)   |
| Model                        | With permanent frame   |
| Height units                 | 47 U   |
| Minimum rack depth supported | 760 mm   |
| Maximum rack depth supported | 940 mm   |
| delivery condition           | fully assembled  |
| Material group               | Steel  |
| Material front door          | Glass  |
| Wall mountable               | no   |
| Demountable                  | yes  |
| Adjustable feet              | yes  |
| Maximum weight capacity      | 600 kg   |
| Protection class (IP Code)   | IP20   |
| Soundproof                   | no   |
| Number of doors              | 1  |
| With front door              | yes  |
| With backside door           | no   |
| With glazed door             | yes  |
| Front                        | Glass door   |
| Rack rails                   | yes  |
| Roof                         | Removable roof   |
| Side panels included         | yes  |

|                                       |                     |
|---------------------------------------|---------------------|
| Removeable side panels                | yes                 |
| Removable front door                  | yes                 |
| Removable back door                   | yes                 |
| Floor                                 | Sliding base plate  |
| Ventilation                           | Passive             |
| RAL colour                            | RAL 7035 Light grey |
| Height                                | 2276 mm             |
| Width                                 | 600 mm              |
| Depth                                 | 1000 mm             |
| Weight                                | 118 kg              |
| Height of packaging<br>(single piece) | 2416 mm             |
| Width of packaging<br>(single piece)  | 680 mm              |
| Depth of packaging<br>(single piece)  | 1080 mm             |
| Package weight (single<br>piece)      | 122.8 kg            |