

# ROLINE 19-inch server rack Pro 26 U, 600x1000 WxD grey

<b>Product No.</b>	26.21.0147
<b>Manufacturer</b>	ROLINE
<b>Manufacturer No.</b>	26.21.0147
<b>EAN (single piece)</b>	7630049601505



## ROLINE 19 inch server cabinet 26 U 600x1000 WxD grey

The server enclosures in the ROLINE Pro series have been specially developed for convenient and flexible network cabling. Inlets with brushes, a slide-on inlet with a foam rubber seal and an additional brush inlet in the base chassis are located on the sides of the roof and base (from 800 mm enclosure width), offering a wide range of possible applications. Perforated single-leaf front doors and double-leaf rear doors, each with a swivel handle and profile half cylinder, ensure improved air circulation. The roof has a perforated cover that allows easy installation of a fan module.

Two pairs of galvanised 19" profile rails are mounted inside the cabinet, which are equipped with height units that can be read in both directions and are adjustable in depth. They are also connected with depth braces. Each cabinet consists of a robust steel construction with a material thickness of up to 2.0 mm. The cabinets are electrostatically powder-coated and available in the standard colours grey (RAL 7035) and black (RAL 9005). Modular lockable and removable side panels (horizontally divided from 42U) and doors improve accessibility. The door hinges can also be changed. The entire construction can be dismantled, meaning that the cabinets can be completely removed if required.

### Technical specifications

Manufacturer	ROLINE
Product group	19"-/10"-Cabinet
Product type	19"-Server cabinet

Colour	grey
Scope of delivery	19-inch server enclosure 26 U, earthing cable set, installation kit for profile half cylinder, 2x spanners, installation set (screws, cage nuts, washers), assembly instructions
Type of profile rail	L-shaped
Modular spacing	482.6 mm (19 inch)
Model	With permanent frame
Height units	26 U
Minimum rack depth supported	675 mm
Maximum rack depth supported	875 mm
delivery condition	fully assembled
Material group	Steel
Material front door	Steel
Material rear door	Steel
Server cabinet	yes
Wall mountable	no
Adjustable feet	yes
Maximum weight capacity	1000 kg
Protection class (IP Code)	IP20
Soundproof	no
Number of doors	2
With front door	yes
With backside door	yes
With glazed door	yes
Front	Steel door with perforation
Backside	Steel door with perforation
Rack rails	yes

Side panels included	yes
Removeable side panels	yes
Removable front door	yes
Removable back door	yes
Ventilation	Passive
RAL colour	RAL 7035 Light grey
Height	1260 mm
Width	600 mm
Depth	1000 mm
Weight	82 kg
Height of packaging (single piece)	1400 mm
Width of packaging (single piece)	1080 mm
Depth of packaging (single piece)	680 mm
Package weight (single piece)	85.6 kg