

# ROLINE 19-inch network cabinet Pro 22 U, 600x800 WxD glass door black

<b>Product No.</b>	26.21.0219
<b>Manufacturer</b>	ROLINE
<b>Manufacturer No.</b>	26.21.0219
<b>EAN (single piece)</b>	7630049602229



## ROLINE 19 inch network cabinet Pro 22 U 600x800 WxD glass door black

The network cabinets in the ROLINE Pro series have been developed to enable particularly convenient and flexible network cabling. With brush inlets in the roof and base area (from 26U and 800 mm cabinet width), a slide-on inlet in the base chassis with foam rubber seal and brush strips above and below the rear door (from 26U), they offer a wide range of possible uses for various application scenarios. Vertical cable ducts with cover, installed next to the profile rails (from 800 mm enclosure width), complete the design. A stepped, removable cover with ventilation slots improves air circulation and allows easy installation of a fan module. Two pairs of galvanised 19" profile rails are installed inside, which can be read in both directions and are adjustable in depth. They are also connected to additional depth struts in the enclosure. Each cabinet consists of a robust steel construction with a material thickness of up to 1.5 mm sheet steel.

The colouring is carried out using electrostatic powder coating in the standard colours grey (RAL 7035) and black (RAL 9005). Modular removable side panels and doors improve accessibility. It is possible to change the door hinge. The cabinets can also be completely dismantled if required.

### Technical specifications

Manufacturer	ROLINE
Product group	19"-/10"-Cabinet
Product type	19"-Floor cabinet

Colour	black
Scope of delivery	19-inch network enclosure Pro 22 U, earthing cable set, installation kit for profile half cylinder, 2x spanners, installation set (screws, cage nuts, washers), instructions
Type of profile rail	L-shaped
Modular spacing	482.6 mm (19 inch)
Model	With permanent frame
Height units	22 U
Minimum rack depth supported	560 mm
Maximum rack depth supported	740 mm
delivery condition	fully assembled
Material group	Steel
Material front door	Glass
Wall mountable	no
Demountable	yes
Adjustable feet	yes
Maximum weight capacity	600 kg
Protection class (IP Code)	IP20
Soundproof	no
Number of doors	1
With front door	yes
With backside door	no
With glazed door	yes
Front	Glass door
Rack rails	yes
Roof	Removable roof
Side panels included	yes

Removeable side panels	yes
Removable front door	yes
Removable back door	yes
Floor	Sliding base plate
Ventilation	Passive
RAL colour	RAL 9005 Jet black
Height	1164 mm
Width	600 mm
Depth	800 mm
Weight	58.6 kg
Height of packaging (single piece)	1310 mm
Width of packaging (single piece)	680 mm
Depth of packaging (single piece)	880 mm
Package weight (single piece)	65 kg