ROLINE 19" Wall Cabinet Basic Plus 15U, 600x600 BxT black

Product No. Manufacturer Manufacturer No. EAN (single piece) 26.21.0292 ROLINE 26.21.0292 7630049602953





ROLINE 19 inch wall-mounted housing Basic Plus with 600 mm depth

The wall-mounted enclosures in the ROLINE Basic Plus series have been specially designed for flexible network cabling. This series represents an ideal balance between the ROLINE PRO and ROLINE Basic series. The base plate and the roof are equipped with a punched cable inlet. In addition, a punched-out area in the roof makes it possible to accommodate a fan module. Inside, a pair of galvanised profile rails with height units of 483 mm (19") are installed, which are also adjustable in depth. The robust steel constructions of the cabinets are made of strong sheet steel and are available powder-coated in grey (RAL 7035) or black (RAL 9005). The side panels are fitted with a quick-release fastener and are removable, which improves accessibility. An optional lock can also be installed in the side panels. Wall mounting is carried out in two simple steps: Firstly, the rear panel is screwed to the wall and then connected to the housing. Optional levelling feet or castors can be used to make the cabinets free-standing.

- Load capacity: 80 kg
- Front door made of tempered glass, lockable
- Side panels are fitted with a quick-release mechanism and are removable
- Roof with cut-out for fan modules
- Cable feed possible on roof and base
- Ventilation slots for passive ventilation and air extraction
- Incl. mounting material
- IP protection class: IP20
- Delivery: assembled

| Technical specifications | | |
|---------------------------------|-----------------------|--|
| Manufacturer | ROLINE | |
| Product group | 19"- / 10" technology | |
| Product type | 19"-wall housing | |
| Colour | black | |
| Type of profile rail | L-shaped | |
| Modular spacing | 482.6 mm (19 inch) | |
| Model | With permanent frame | |
| Height units | 15 U | |
| Minimum rack depth supported | 320 mm | |
| Maximum rack depth supported | 450 mm | |
| Delivery condition | fully assembled | |
| Demountable | yes | |
| Material group | Steel | |
| Material front door | Glass | |
| Wall mountable | yes | |
| Adjustable feets | no | |
| Maximum weight capacity | 80 kg | |
| Protection class (IP Code) | IP20 | |
| Soundproof | no | |
| Number of doors | 1 | |
| With front door | yes | |
| With backside door | no | |
| With glazed door | yes | |
| Front | Glass door | |
| Rack rails | yes | |
| Side panels included | yes | |

| Removeable side panels | yes |
|---------------------------------------|--------------------|
| Removable front door | yes |
| Removable back door | no |
| Ventilation | Passive |
| RAL colour | RAL 9005 Jet black |
| Height | 779 mm |
| Width | 600 mm |
| Depth | 600 mm |
| Weight | 22 kg |
| Height of packaging (single piece) | 800 mm |
| Width of packaging (single piece) | 630 mm |
| Depth of packaging (single piece) | 935 mm |
| Package weight (single piece) | 24 kg |