

VALUE UPS, Line-Interactive, 400VA, USB Port

Product No. 19.99.3424
Manufacturer VALUE
Manufacturer No. 19.99.3424
EAN (single piece) 7611990130085



Quality Protection for Small Servers, Workstation & PC

- Line interactive design
- Boost and buck AVR (Auto voltage regulation)
- Fully digitized microprocessor controlled
- Energy saving function (UPS green mode)
- 50/60Hz frequency auto sensing and selection
- Cold start function (DC power on)
- Lightning and surge protection
- Short circuit and overload protection
- Advanced battery management (ABM technology)
- Tel/Modem internet surge suppression
- Smart USB communication port
- Automatically charging when UPS off
- History record of power failure events
- Back up, on-line, battery status, power status display by software
- Schedule shutdown & reboot
- Windows 98/Me/NT/2000/XP/2003/7/8

Technical specifications

Manufacturer	VALUE
Product group	UPS
Product type	UPS Line Interactive
Colour	black

Scope of delivery	UPS, Software, Cable-Set
Classification (IEC 62040-3)	VI-SS-333
UPS technology	Line Interactive
Power class	100 ... 500 VA
Output (VA/W)	400 / 240
Efficiency	95 %
Backup time	4 min
Backup time full/half-load	4 / 7 min
Dimensions (HxWxD)	135 x 97 x 320 mm
Mounting form	Tower
Voltage (input)	230 V
Voltage (output)	230 V
Output voltage regulation	± 15 %
Frequency	50 Hz
Connector type (input)	cold connector IEC320 C 14
Outputs	2
Connector type (output)	2x cold connector IEC320 C 13
Phase in/output	230V/230V / 50Hz
Over current protection	EMI,- RFI-Filter
Max. quantity of delay expansion units	0
Slots for adapter card	0
Interface	USB
USB 2.0 Interface	yes
Hot swap batteries	no
Bypass	no
Additional over current protector	Telephone/Fax

Activity	LED
Activity LED	1 LED
Activity Display	--
incl.Management Software	Windows
Internal cooling	Passive
Ambient temperature	0-40°C
Operating temperature min.	0 °C
Operating temperature max.	40 °C
Height	135 mm
Width	97 mm
Depth	320 mm
Weight	4.5 kg
Height of packaging (single piece)	230 mm
Width of packaging (single piece)	150 mm
Depth of packaging (single piece)	380 mm
Package weight (single piece)	5.98 kg

Back up time	
Capacity (VA / W)	Minutes (manufacturer's specifications)
400 / 240	4
360 / 216	5
320 / 192	6
280 / 168	8
240 / 144	12
200 / 120	15

160 / 96	22
120 / 72	36
80 / 48	63
40 / 24	137