

VALUE S/FTP (PiMF) Patch Cord, Cat.6 (Class E), green, 3 m

Product No. 21.99.1353
Manufacturer VALUE
Manufacturer No. 21.99.1353
EAN (single piece) 7611990177554



Prepared shielded Twisted Pair cable with RJ-45 connectors on both sides. Used as patch cable in wiring cabinet or as direct connection cable between devices. Flexible cable suitable for narrow bending. Contact settings 1:1, according to EIA/TIA 568, 8 wires. Construction: 8 wires stranded copper wire, braided shield. Impedance: 100 Ohm. For a structured cabling system we recommend to use the following components: ROLINE Cat.6 S/FTP Cable, Solid Wire, AWG23: 21.15.0890 (100 m), 21.15.0891 (300 m). VALUE Cat.6 Flush/Surface Mount Wall Jack, shielded, white: 25.99.8492/25.99.8392. VALUE Cat.6 19" Patch Panel, 24 Ports, shielded: 26.99.0353 (black), 26.99.0354 (grey). VALUE Cat.6 S/FTP Patch Cord, grey, 5 m: 21.99.0805. Our in-house laboratory has tested this cable-plug combination, in a Channel of 100 meters, in compliance with Class E specifications.

| Technical specifications | |
|--------------------------|--------------------------|
| Manufacturer | VALUE |
| Product group | Twisted Pair Cable |
| Product type | S / FTP patch cable PiMF |
| Colour | green |
| Length | 3 m |

| | |
|---------------------------------------|----------------|
| Shield type | PiMF |
| Transfer quality | Cat6 / Class E |
| Impedance | 100 Ohm |
| Quantity of wires | 8 |
| Conductor cross section (AWG) | AWG 27 |
| Conductor type | Stranded |
| Crossed | no |
| Assignment | 1:1 |
| Locking lever | no |
| Anti-kink sleeve | Moulded-on |
| Colour (Spout) | green |
| Cable LSOH | no |
| Side 1 Connector Type | RJ-45 |
| Side 1 Connector Gender | Male |
| Side 2 Connector Type | RJ-45 |
| Side 2 Connector Gender | Male |
| Connector Type RJ45 | Standard |
| Operating temperature min. | -20 °C |
| Operating temperature max. | 60 °C |
| Weight | 86.5 g |
| Height of packaging (single piece) | 20 mm |
| Width of packaging (single piece) | 120 mm |
| Depth of packaging (single piece) | 120 mm |

| | |
|-------------------------------|----------|
| Package weight (single piece) | 0.154 kg |
|-------------------------------|----------|