

# VALUE S/FTP (PiMF) Patch Cord, Cat.6 (Class E), black, 7 m

|                           |               |
|---------------------------|---------------|
| <b>Product No.</b>        | 21.99.1375    |
| <b>Manufacturer</b>       | VALUE         |
| <b>Manufacturer No.</b>   | 21.99.1375    |
| <b>EAN (single piece)</b> | 7611990191048 |



Prepared shielded Twisted Pair cable with RJ-45 connectors on both sides. Used as patch cable in wiring cabinet or as direct connection cable between devices. Flexible cable suitable for narrow bending. Contact settings 1:1, according to EIA/TIA 568, 8 wires. Construction: 8 wires stranded copper wire, braided shield. Impedance: 100 Ohm. For a structured cabling system we recommend to use the following components: ROLINE Cat.6 S/FTP Cable, Solid Wire, AWG23: 21.15.0890 (100 m), 21.15.0891 (300 m). VALUE Cat.6 Flush/Surface Mount Wall Jack, shielded, white: 25.99.8492/25.99.8392. VALUE Cat.6 19" Patch Panel, 24 Ports, shielded: 26.99.0353 (black), 26.99.0354 (grey). VALUE Cat.6 S/FTP Patch Cord, grey, 5 m: 21.99.0805. Our in-house laboratory has tested this cable-plug combination, in a Channel of 100 meters, in compliance with Class E specifications.

## Technical specifications

|               |                          |
|---------------|--------------------------|
| Manufacturer  | VALUE                    |
| Product group | Twisted Pair Cable       |
| Product type  | S / FTP patch cable PiMF |
| Colour        | black                    |
| Length        | 7 m                      |

|                                    |                |
|------------------------------------|----------------|
| Shield type                        | PiMF           |
| Transfer quality                   | Cat6 / Class E |
| Impedance                          | 100 Ohm        |
| Quantity of wires                  | 8              |
| Conductor type                     | Wire           |
| Crossed                            | No             |
| Colour (Spout)                     | black          |
| Cable LSOH                         | No             |
| Side 1 Connector Type              | RJ-45          |
| Side 1 Connector Gender            | Male           |
| Side 2 Connector Type              | RJ-45          |
| Side 2 Connector Gender            | Male           |
| Connector Type RJ45                | Standard       |
| Operating temperature min.         | -20 °C         |
| Operating temperature max.         | 60 °C          |
| Weight                             | 199 g          |
| Height of packaging (single piece) | 35 mm          |
| Width of packaging (single piece)  | 155 mm         |
| Depth of packaging (single piece)  | 150 mm         |
| Package weight (single piece)      | 0.22 kg        |