

# VALUE S/FTP (PiMF) Patch Cord, Cat.6 (Class E), green, 10 m

**Product No.** 21.99.1383  
**Manufacturer** VALUE  
**Manufacturer No.** 21.99.1383  
**EAN (single piece)** 7611990177653



Prepared shielded Twisted Pair cable with RJ-45 connectors on both sides. Used as patch cable in wiring cabinet or as direct connection cable between devices. Flexible cable suitable for narrow bending. Contact settings 1:1, according to EIA/TIA 568, 8 wires. Construction: 8 wires stranded copper wire, braided shield. Impedance: 100 Ohm. For a structured cabling system we recommend to use the following components: ROLINE Cat.6 S/FTP Cable, Solid Wire, AWG23: 21.15.0890 (100 m), 21.15.0891 (300 m). VALUE Cat.6 Flush/Surface Mount Wall Jack, shielded, white: 25.99.8492/25.99.8392. VALUE Cat.6 19" Patch Panel, 24 Ports, shielded: 26.99.0353 (black), 26.99.0354 (grey). VALUE Cat.6 S/FTP Patch Cord, grey, 5 m: 21.99.0805. Our in-house laboratory has tested this cable-plug combination, in a Channel of 100 meters, in compliance with Class E specifications.

| Technical specifications |                          |
|--------------------------|--------------------------|
| Manufacturer             | VALUE                    |
| Product group            | Twisted Pair Cable       |
| Product type             | S / FTP patch cable PiMF |
| Colour                   | green                    |
| Length                   | 10 m                     |

|                                       |                |
|---------------------------------------|----------------|
| Shield type                           | PiMF           |
| Transfer quality                      | Cat6 / Class E |
| Impedance                             | 100 Ohm        |
| Quantity of wires                     | 8              |
| Conductor cross section<br>(AWG)      | AWG 27         |
| Conductor type                        | Stranded       |
| Crossed                               | no             |
| Assignment                            | 1:1            |
| Locking lever                         | no             |
| Anti-kink sleeve                      | Moulded-on     |
| Colour (Spout)                        | green          |
| Cable LSOH                            | no             |
| Side 1 Connector Type                 | RJ-45          |
| Side 1 Connector<br>Gender            | Male           |
| Side 2 Connector Type                 | RJ-45          |
| Side 2 Connector<br>Gender            | Male           |
| Connector Type RJ45                   | Standard       |
| Operating temperature<br>min.         | -20 °C         |
| Operating temperature<br>max.         | 60 °C          |
| Weight                                | 268.3 g        |
| Height of packaging<br>(single piece) | 35 mm          |
| Width of packaging<br>(single piece)  | 170 mm         |
| Depth of packaging<br>(single piece)  | 170 mm         |

---

|                               |         |
|-------------------------------|---------|
| Package weight (single piece) | 0.36 kg |
|-------------------------------|---------|