## VALUE S/FTP Patch Cord Cat.6A (Class EA), green, 20

m

Product No. Manufacturer Manufacturer No. EAN (single piece)	21.99.1949 VALUE 21.99.1949 7611990123131	Value
	UTP = U/UTP       FTP = F/UTP         UTP = U/UTP       FTP = F/UTP         SRFTP (Cat.6e)       S/FTP (Cat.6)         SRFTP (Cat.6e)       S/FTP (P/MF)         Green: aluminium cited foil : Red: timed copper braid	
Cat.6A Class EA	LSOH	

The cheap solution for data transfer rates of up to 10 Gbit/s and a bandwidth of 500 MHz. Patch cable for networking connections between devices. Prepared shielded Twisted Pair cable (PiMF) with RJ-45 connectors on both ends. Durable due to moulded kink protection. Flexible cable, suitable for narrow bending. Impedance: 100 Ohm. Contact settings 1:1, in accordance with the EIA/TIA 568 standard. Construction: 8 lines, pairs shielded with aluminium foil, complete braided shielding.

## For a structured shielded Cat.6a cabling system we recommend to use the following components:

VALUE Cat.6a S/FTP Cable, Solid Wire, 100 m: 21.99.0881.
Flush Mount Wall Jack for Keystones: 25.16.8579.
Surface Wall Mount Frame: 25.16.8484.
VALUE Cat.6a Keystone, RJ-45, shielded: 26.99.0366.
19" Keystone Patch Panel: 26.11.0359.
VALUE Cat.6a S/FTP Patch Cord, 5 m: 21.99.0865.

Technical specifications		
Manufacturer	VALUE	

Product group	Twisted Pair Cable
Product type	S/FTP Patchcord
Colour	green
Length	20 m
Shield type	SFTP
Transfer quality	Cat6A / Class EA
Quantity of wires	8
Conductor cross section (AWG)	AWG 27
Conductor type	Stranded
Crossed	no
Locking lever	yes
Anti-kink sleeve	Moulded-on
Colour (Spout)	green
Cable LSOH	yes
Side 1 Connector Type	RJ-45
Side 1 Connector Gender	Male
Side 2 Connector Type	RJ-45
Side 2 Connector Gender	Male
Connector Type RJ45	Standard
Weight	578.8 g
Height of packaging (single piece)	50 mm
Width of packaging (single piece)	190 mm
Depth of packaging (single piece)	190 mm
Package weight (single piece)	0.67 kg