

# VALUE S/FTP Patch Cord Cat.6A (Class EA), black, 10 m

|                    |               |
|--------------------|---------------|
| Product No.        | 21.99.1967    |
| Manufacturer       | VALUE         |
| Manufacturer No.   | 21.99.1967    |
| EAN (single piece) | 7611990124152 |



Cat.6A  
Class EA

S/FTP

LSOH

The cheap solution for data transfer rates of up to 10 Gbit/s and a bandwidth of 500 MHz. Patch cable for networking connections between devices. Prepared shielded Twisted Pair cable (PIMF) with RJ-45 connectors on both ends. Durable due to moulded kink protection. Flexible cable, suitable for narrow bending. Impedance: 100 Ohm. Contact settings 1:1, in accordance with the EIA/TIA 568 standard. Construction: 8 lines, pairs shielded with aluminium foil, complete braided shielding.

**For a structured shielded Cat.6a cabling system we recommend to use the following components:**

- VALUE Cat.6a S/FTP Cable, Solid Wire, 100 m: 21.99.0881.
- Flush Mount Wall Jack for Keystones: 25.16.8579.
- Surface Wall Mount Frame: 25.16.8484.
- VALUE Cat.6a Keystone, RJ-45, shielded: 26.99.0366.
- 19" Keystone Patch Panel: 26.11.0359.
- VALUE Cat.6a S/FTP Patch Cord, 5 m: 21.99.0865.

| Technical specifications |       |
|--------------------------|-------|
| Manufacturer             | VALUE |

|                                    |                         |
|------------------------------------|-------------------------|
| Product group                      | Twisted Pair Cable      |
| Product type                       | S/FTP patch cord (PiMF) |
| Colour                             | black                   |
| Length                             | 10 m                    |
| Shield type                        | S/FTP (PiMF)            |
| Transfer quality                   | Cat6A / Class EA        |
| Quantity of wires                  | 8                       |
| Conductor cross section (AWG)      | AWG 27                  |
| Conductor type                     | Stranded                |
| Crossed                            | no                      |
| Locking lever                      | yes                     |
| Anti-kink sleeve                   | Moulded-on              |
| Colour (Spout)                     | black                   |
| Cable LSOH                         | yes                     |
| Side 1 Connector Type              | RJ-45                   |
| Side 1 Connector Gender            | Male                    |
| Side 2 Connector Type              | RJ-45                   |
| Side 2 Connector Gender            | Male                    |
| Connector Type RJ45                | Standard                |
| Weight                             | 296.8 g                 |
| Height of packaging (single piece) | 40 mm                   |
| Width of packaging (single piece)  | 200 mm                  |
| Depth of packaging (single piece)  | 200 mm                  |
| Package weight (single piece)      | 0.302 kg                |