

# VALUE Fibre Optic Jumper Cable, 50/125µm, LC/SC, OM3, turquoise, 10 m

|                           |               |
|---------------------------|---------------|
| <b>Product No.</b>        | 21.99.8718    |
| <b>Manufacturer</b>       | VALUE         |
| <b>Manufacturer No.</b>   | 21.99.8718    |
| <b>EAN (single piece)</b> | 7611990196593 |



## VALUE fiber optic patch cord in OM3 quality for high-performance fiber optic cabling

- VALUE Fibre Optic Jumper Cables with OM3 quality for high performance wiring
- Duplex Cable with fibre type Multi-mode 50/125µm, OM3
- Available length: 0,5m, 1m, 2m, 3m, 5m and 10m
- Color: turquoise

### Technical specifications

|                       |                               |
|-----------------------|-------------------------------|
| Manufacturer          | VALUE                         |
| Product group         | Fibre optic cable             |
| Product type          | Fibre Optic Jumper Cables OM3 |
| Colour                | turquoise                     |
| Length                | 10 m                          |
| Quantity of fibre     | 2                             |
| Conductor composition | Compact conductor             |
| Cable type            | Duplex Cable                  |
| External cable        | no                            |
| Fibre section         | Multi mode 50/125µm OM3       |

|                                       |           |
|---------------------------------------|-----------|
| Connection ports                      | LC / SC   |
| Side 1 Connector Type                 | LC        |
| Side 2 Connector Type                 | SC        |
| Min. Bending radius,<br>static        | 30 mm     |
| Min. Bending radius,<br>dynamic       | 60 mm     |
| Colour (Cable)                        | turquoise |
| Aramid strain relief                  | yes       |
| External cable diameter               | 2,8x6 mm  |
| Mantle of external cable              | PVC       |
| Cable LSOH                            | no        |
| Max. insertion loss                   | 0.3 dB    |
| Min. return loss                      | 30 dB     |
| Weight                                | 135.7 g   |
| Height of packaging<br>(single piece) | 20 mm     |
| Width of packaging<br>(single piece)  | 200 mm    |
| Depth of packaging<br>(single piece)  | 330 mm    |
| Package weight (single<br>piece)      | 0.2 kg    |