## VALUE Fibre Optic Jumper Cable, 50/125μm, LC/ST, OM4, violet, 2 m

7611990198412

Product No.21.99.8772ManufacturerVALUEManufacturer No.21.99.8772





EAN (single piece)

OM4 fiber for existing 1 and 10 Gbit/s applications as well as future 40 and 100 Gbit/s systems. Allows extended reach upwards of 550 meters at 10 Gbit/s for ultra long building backbones and medium length campus backbones. With an laser bandwidth of 4700 MHz-km (more than double the IEEE requirement for 10 Gbit/s 300 meter support), the OM4 fiber is also especially well suited for shorter reach in data centers and high performance computing applications.

- VALUE OM4 Fibre Optic Jumper cable with fiber type 50/125 μm
- Color: purple

Technical specifications		
VALUE		
Fibre optic cable		
Fibre Optic Jumper Cables OM4		
violet		
2 m		
2		
Compact conductor		
Duplex Cable		

External cable no Fibre section 50/125µm OM4  Connection ports LC / ST  Side 1 Connector Type LC  Side 2 Connector Type ST  Aramid strain relief yes  External cable diameter 2,8x6 mm  Mantle of external cable PVC  Cable LSOH no  Weight 38.9 g  Height of packaging (single piece)  Width of packaging (single piece)  Depth of packaging (single piece)  Package weight (single piece)  Package weight (single piece)  Double Solution of the strain of the s		
Connection ports  LC / ST  Side 1 Connector Type  LC  Side 2 Connector Type  Aramid strain relief  yes  External cable diameter  Z,8x6 mm  Mantle of external cable  PVC  Cable LSOH  no  Weight  38.9 g  Height of packaging (single piece)  Width of packaging (single piece)  Depth of packaging (single piece)  Package weight (single)  0.08 kg	External cable	no
Side 1 Connector Type LC  Side 2 Connector Type ST  Aramid strain relief yes  External cable diameter 2,8x6 mm  Mantle of external cable PVC  Cable LSOH no  Weight 38.9 g  Height of packaging (single piece)  Width of packaging (single piece)  Depth of packaging (single piece)  Package weight (single 0.08 kg	Fibre section	50/125μm OM4
Side 2 Connector Type ST  Aramid strain relief yes  External cable diameter 2,8x6 mm  Mantle of external cable PVC  Cable LSOH no  Weight 38.9 g  Height of packaging (single piece)  Width of packaging (single piece)  Depth of packaging (single piece)  Package weight (single 0.08 kg	Connection ports	LC / ST
Aramid strain relief yes  External cable diameter 2,8x6 mm  Mantle of external cable PVC  Cable LSOH no  Weight 38.9 g  Height of packaging (single piece)  Width of packaging (single piece)  Depth of packaging (single piece)  Package weight (single 0.08 kg	Side 1 Connector Type	LC
External cable diameter 2,8x6 mm  Mantle of external cable PVC  Cable LSOH no  Weight 38.9 g  Height of packaging 20 mm (single piece)  Width of packaging 150 mm (single piece)  Depth of packaging 130 mm (single piece)  Package weight (single 0.08 kg	Side 2 Connector Type	ST
Mantle of external cable PVC  Cable LSOH no  Weight 38.9 g  Height of packaging (single piece)  Width of packaging (single piece)  Depth of packaging (single piece)  Package weight (single 0.08 kg	Aramid strain relief	yes
Cable LSOH no  Weight 38.9 g  Height of packaging (single piece)  Width of packaging (single piece)  Depth of packaging (single piece)  Package weight (single 0.08 kg	External cable diameter	2,8x6 mm
Weight 38.9 g  Height of packaging (single piece)  Width of packaging (single piece)  Depth of packaging (single piece)  Package weight (single 0.08 kg	Mantle of external cable	PVC
Height of packaging (single piece)  Width of packaging (single piece)  Depth of packaging (single piece)  Package weight (single 0.08 kg	Cable LSOH	no
(single piece)  Width of packaging (single piece)  Depth of packaging (single piece)  Package weight (single 0.08 kg	Weight	38.9 g
(single piece)  Depth of packaging 130 mm (single piece)  Package weight (single 0.08 kg		20 mm
(single piece)  Package weight (single 0.08 kg		150 mm
		130 mm
		0.08 kg