VALUE 19" Wall Mount Rack 6U, 368 x 570 x 600mm (HxWxD), black

Product No. 26.99.0147

Manufacturer VALUE

Manufacturer No. 26.99.0147

EAN (single piece) 7611990137763







- VALUE stand/wall mount cabinets for the installation of active and passive network components
- Toughened glass front with lock with rotary handle, the direction of opening the door can be changed according to the requirement, the opening degree of the door is more than 180°
- Quick open side door, convenient for equipment installation and maintaining
- One cable channel on the top and the other on the bottom
- 19" standard installation, installation depth can be adjusted according to the requirement
- Colour: black (RAL 7021)
- Max. Load (distributed): 60 kg
- · Remark: Delivery as an assembly set
- Contents: Wall mount rack, grounding set, installation material

For small network installations, even a half-height network cabinet is often too big, especially since only a parking space has to be found. In such cases, wall enclosures are the better solution. They provide enough space for some switches and patch panels and do not require space on the floor due to wall mounting. In addition, the network administrator can easily read the status of the switches without compromising their knees, or patch a patch cable without slipping on the ground.

The VALUE wall enclosures prove that such practical solutions can also be attractive. The black, slightly shiny housings are quite office-appropriate. A generous glass insert in the door allows a clear view of all built-in active and passive components even when the door is closed. Both the door and the side walls can be removed for optimum access to the inside of the housing; The cable feed can be carried out from above or below. The door of the VALUE wall housing comes with lockable swivel lever.

Front Glass door with frame Side panel Plug door 19" level Ahead	Technical specifications		
Product type 19"-wall housing Colour black Scope of delivery Wall mount rack, grounding set, installation material Modular spacing 482.6 mm (19 inch) Height units 6 U Maximum rack depth supported Delivery condition Flatpack, disassembled Demountable yes Server cabinet no Wall mountable yes Socket no Socket with tilt protection Dimensions (HxWxD) 368 x 570 x 600 mm W/o socket Maximum weight capacity Number of doors 1 With front door yes With glazed door yes Front Glass door with frame Side panel Plug door 19" level Ahead	Manufacturer	VALUE	
Colour black Scope of delivery Wall mount rack, grounding set, installation material Modular spacing 482.6 mm (19 inch) Height units 6 U Maximum rack depth supported Delivery condition Flatpack, disassembled Demountable yes Server cabinet no Wall mountable yes Socket no Socket with tilt protection Dimensions (HxWxD) 368 x 570 x 600 mm W/o socket Maximum weight capacity Number of doors 1 With front door yes With backside door no With glazed door With glazed door 19" level Ahead	Product group	19"-/10"-Cabinet	
Scope of delivery Wall mount rack, grounding set, installation material Modular spacing 482.6 mm (19 inch) Height units 6 U Maximum rack depth supported Delivery condition Flatpack, disassembled Demountable yes Server cabinet no Wall mountable yes Socket no Socket with tilt no Dimensions (HxWxD) 368 x 570 x 600 mm W/o socket Maximum weight capacity Number of doors 1 With front door yes With backside door no With glazed door With glazed door Flour Glass door with frame Side panel Plug door 19" level Ahead	Product type	19"-wall housing	
Modular spacing 482.6 mm (19 inch) Height units 6 U Maximum rack depth supported Delivery condition Flatpack, disassembled Demountable yes Server cabinet no Wall mountable yes Socket no Socket with tilt protection Dimensions (HxWxD) 368 x 570 x 600 mm w/o socket Maximum weight capacity Number of doors 1 With front door yes With backside door no With glazed door yes Front Glass door with frame Side panel Plug door 19" level Ahead	Colour	black	
Height units 6 U Maximum rack depth supported Delivery condition Flatpack, disassembled Demountable yes Server cabinet no Wall mountable yes Socket no Socket with tilt no Dimensions (HxWxD) 368 x 570 x 600 mm W/o socket Maximum weight capacity Number of doors 1 With front door yes With backside door no With glazed door yes Front Glass door with frame Side panel Plug door 19" level Ahead	Scope of delivery	Wall mount rack, grounding set, installation material	
Maximum rack depth supported Delivery condition Flatpack, disassembled Demountable yes Server cabinet no Wall mountable yes Socket no Socket with tilt no Dimensions (HxWxD) 368 x 570 x 600 mm W/o socket Maximum weight capacity Number of doors 1 With front door yes With backside door no With glazed door yes Front Glass door with frame Side panel Plug door 19" level Ahead	Modular spacing	482.6 mm (19 inch)	
supported Delivery condition Flatpack, disassembled Demountable yes Server cabinet no Wall mountable yes Socket no Socket with tilt no protection Dimensions (HxWxD) 368 x 570 x 600 mm w/o socket Maximum weight capacity Number of doors 1 With front door yes With backside door no With glazed door yes Front Glass door with frame Side panel Plug door 19" level Ahead	Height units	6 U	
Demountable yes Server cabinet no Wall mountable yes Socket no Socket with tilt no protection Dimensions (HxWxD) 368 x 570 x 600 mm w/o socket Maximum weight capacity Number of doors 1 With front door yes With backside door no With glazed door yes Front Glass door with frame Side panel Plug door 19" level Ahead	-	500 mm	
Server cabinet no Wall mountable yes Socket no Socket with tilt no protection Dimensions (HxWxD) 368 x 570 x 600 mm w/o socket Maximum weight capacity Number of doors 1 With front door yes With backside door no With glazed door yes Front Glass door with frame Side panel Plug door 19" level Ahead	Delivery condition	Flatpack, disassembled	
Wall mountable yes Socket no Socket with tilt no protection Dimensions (HxWxD) 368 x 570 x 600 mm w/o socket Maximum weight capacity Number of doors 1 With front door yes With backside door no With glazed door yes Front Glass door with frame Side panel Plug door 19" level Ahead	Demountable	yes	
Socket in o Socket with tilt no protection Dimensions (HxWxD) 368 x 570 x 600 mm w/o socket Maximum weight capacity Number of doors 1 With front door yes With backside door no With glazed door yes Front Glass door with frame Side panel Plug door 19" level Ahead	Server cabinet	no	
Socket with tilt protection Dimensions (HxWxD) 368 x 570 x 600 mm w/o socket Maximum weight 60 kg capacity Number of doors 1 With front door yes With backside door no With glazed door yes Front Glass door with frame Side panel Plug door 19" level Ahead	Wall mountable	yes	
protection Dimensions (HxWxD) 368 x 570 x 600 mm W/o socket Maximum weight 60 kg capacity Number of doors 1 With front door yes With backside door no With glazed door yes Front Glass door with frame Side panel Plug door 19" level Ahead	Socket	no	
Maximum weight 60 kg capacity Number of doors 1 With front door yes With backside door no With glazed door yes Front Glass door with frame Side panel Plug door 19" level Ahead		no	
Number of doors 1 With front door yes With backside door no With glazed door yes Front Glass door with frame Side panel Plug door 19" level Ahead		368 x 570 x 600 mm	
With front door yes With backside door no With glazed door yes Front Glass door with frame Side panel Plug door 19" level Ahead	_	60 kg	
With backside door no With glazed door yes Front Glass door with frame Side panel Plug door 19" level Ahead	Number of doors	1	
With glazed door yes Front Glass door with frame Side panel Plug door 19" level Ahead	With front door	yes	
Front Glass door with frame Side panel Plug door 19" level Ahead	With backside door	no	
Side panel Plug door 19" level Ahead	With glazed door	yes	
19" level Ahead	Front	Glass door with frame	
	Side panel	Plug door	
Roof Cable entry possibility	19" level	Ahead	
	Roof	Cable entry possibility	
Roof raised no	Roof raised	no	
Floor Closed	Floor	Closed	

Ventilation	Passive
Fan ready	yes
Grounding set mounted	no
Colour (Cabinet)	black
Colour (Covering)	black
Colour	black
Height	368 mm
Width	570 mm
Depth	600 mm
Weight	17.41 kg
Height of packaging (single piece)	300 mm
Width of packaging (single piece)	600 mm
Depth of packaging (single piece)	570 mm
Package weight (single piece)	18.5 kg