VALUE Network Cabinet 42U, 2000x800x800 mm, damaged

Product No.

Manufacturer

Manufacturer No.

26.99.0811 VALUE









ATTENTION: This is a damaged product. Fault description: Individual paint damage & scratches.

VALUE 19"-Cabinet, black, in 42 U, as Cabling Cabinet

- Cabling Cabinet in BxT 800x800mm with a glass door on the front side and a back door in sheet steel
- Two pairs of 19"-profiles
- All doors are lockable with single point locking
- 4 castors as well as 4 adjustable feet
- Demountable side panels, convenient for installation and maintenance
- Top cover of Cabling Cabinet with cable entry opening possibility and with 4 cooling fans included
- 3 fixed shelfs and a pair of vertical cable management

Features:

Front Door: Glass door + green color decorative strip and small round lock

Back Door: Flat steel with small round lock, with 4pcs cooling fan

Comply with ANSI/EIA

• Material: SPCC Cold Rolled Steel

Static loading: 800kg

• 4 fan units: 1 set

• Fixed shelf: 3 pcs

Management slot: 2 pcs

Castor: 4 pcsM12 feet: 4pcs

Remark: Picture similar

Technical specifications	
Manufacturer	VALUE
Product group	19"-/10"-Cabinet
Product type	19"-Floor cabinet
Colour	black
Type of profile rail	L-shaped
Modular spacing	482.6 mm (19 inch)
Height units	42 U
Maximum rack depth supported	650 mm
Demountable	yes
Material group	Steel
Material front door	Glass
Material rear door	Steel
Server cabinet	no
Socket	no
Socket with tilt protection	no
Dimensions (HxWxD) w/o socket	2000 x 800 x 800 mm
Adjustable feets	yes
Maximum weight capacity	800 kg
Protection class (IP Code)	IP20
Number of doors	2
With front door	yes

With glazed door	yes
Front	Glass door with frame
Backside	Steel door
Side panel	Plug door
19" level	Ahead and behind
Roof	Cable entry possibility
Roof raised	no
Floor	Closed
Ventilation	Active
Fan ready	yes
Grounding set mounted	no
Colour (Cabinet)	black
Colour (Covering)	black
Height	2000 mm
Width	800 mm
Depth	800 mm
Weight	136.34 kg
Height of packaging (single piece)	0 mm
Width of packaging (single piece)	0 mm
Depth of packaging (single piece)	0 mm
Package weight (single piece)	0 kg