

VALUE 19" Wall Cabinet 15U , 600x450mm, black

Product No.	26.99.0826
Manufacturer	VALUE
Manufacturer No.	26.99.0826
EAN (single piece)	7630049603295



VALUE wall-mounted enclosures are designed for flexible network cabling and feature punched cable inlets in the bottom and top as well as fan preparation. The robust steel construction is powder-coated and equipped with removable side panels with quick-release fasteners. Optional locks can be integrated for added security. The cabinet is delivered as a kit and can be assembled quickly and easily.

The VALUE wall-mounted enclosures have been specially developed for flexible network cabling. Both the base plate and the roof are equipped with punched cable inlets. In addition, there is a punched area in the roof to accommodate a fan module.

Inside, there is a pair of galvanized profile rails with 483 mm (19") height units, which are also adjustable in depth. An additional pair of profile rails can be retrofitted. The robust steel construction is made of high-quality sheet steel and is available in black (RAL 9005) powder coating.

The side panels are equipped with a quick-release fastener and are removable, which significantly facilitates accessibility during operation. Locks can be integrated into the side panels as an option. Wall mounting is carried out in two simple steps: first, the rear panel is attached to the wall, then the enclosure is mounted. Leveling feet or casters can be attached as an option to allow the enclosure to be used as a free-standing unit.

- Load capacity: 80 kg
- Front door made of tempered glass, lockable
- Side panels are equipped with quick-release fasteners and are removable
- Roof with cut-out for fan modules
- Cable entry possible at roof and floor
- Ventilation slots for passive ventilation
- Includes mounting hardware

- Protection class: IP20
- Delivery: flatpack

Technical specifications	
Manufacturer	VALUE
Product group	19"/-10"-Cabinet
Product type	19"-wall housing
Colour	black
Scope of delivery	VALUE wall housing (flatpack), grounding cable set, 2x keys, installation instructions
Type of profile rail	L-shaped
Modular spacing	482.6 mm (19 inch)
Height units	15 U
Minimum rack depth supported	305 mm
Maximum rack depth supported	350 mm
Delivery condition	Flatpack, disassembled
Demountable	yes
Material group	Steel
Material front door	Glass
Wall mountable	yes
Adjustable feets	no
Maximum weight capacity	80 kg
Protection class (IP Code)	IP20
Number of doors	1
With front door	yes
With backside door	no
With glazed door	yes
Front	Glass door

Rack rails	yes
19" level	Ahead
Side panels included	yes
Removeable side panels	yes
Removable front door	yes
Removable back door	no
Ventilation	Passive
Fan ready	yes
RAL colour	RAL 9005 Jet black
Height	779 mm
Width	600 mm
Depth	450 mm
Weight	18.2 kg
Height of packaging (single piece)	220 mm
Width of packaging (single piece)	640 mm
Depth of packaging (single piece)	480 mm
Package weight (single piece)	0 kg