ROLINE GREEN USB 3.2 Gen 2 Cable, PD (Power Delivery) 20V5A, with Emark, C-C, M/M, black, 0.5 m

Product No. 11.44.9052

Manufacturer ROLINE GREEN

11.44.9052

11.44.9052

EAN (single piece) 7630049619876









Full-featured USB 3.1 / USB 3.2 Gen 2 cable with a data transmission rate of up to 10 Gbit/s and full Power Delivery support of up to 20V 5A!

- High quality USB 3.1 / USB 3.2 Gen 2 cable with improved shielding
- With the new reversible Type C connectors at both ends
- Gold-plated contacts for low wear at high plugging cycles
- Suitable for data transfer rates of up to 10 Gbit/s
- Supports USB Power Delivery to 20V / 5A
- Supports video transfer

ROLINE GREEN products are marked only with a paper tag and build with halogenfree TPE material, without plastic bags and without plastic cable straps for use in eco-friendly environments.

Note: According to the current specifications of USB.org we have adapted the technical data of our USB 3 products. The new designation for the already known USB specifications has been changed to USB 3.2 Gen 1 (formerly USB 3.0 / USB 3.1 Gen 1) and USB 3.2 Gen 2 (formerly USB 3.1 / USB 3.1 Gen 2).

Technical specifications		
Manufacturer	ROLINE GREEN	
Product group	Cable	
Product type	USB 3.2 Cable	

Colour	black
Length	0.5 m
Scope of delivery	Cable without plastic bag, only marked with a paper label
Transfer quality	USB 3.2 Gen 2 SuperSpeed 10 Gbit/s (USB 3.1 Gen 2, USB 3.1)
Connection ports	USB Type C (USB-C) Male / USB Type C (USB-C) Male
Side 1 Connector Type	USB Type C (USB-C)
Side 1 Connector Gender	Male
Side 2 Connector Type	USB Type C (USB-C)
Side 2 Connector Gender	Male
Colour (Cable)	black
Maximum data transfer rate	10 Gbit/s
Area of application	External
Supported charging technology	USB-PD - USB Power Delivery
Power (max.)	100 W
Cable shielding	Screened
Hand locking screws	no
Material (external cable mantle)	TPE
Cable LSOH	halogen-free
Weight	25.3 g
Height of packaging (single piece)	30 mm
Width of packaging (single piece)	100 mm
Depth of packaging (single piece)	120 mm
Package weight (single piece)	0.025 kg