
## ROLINE GREEN U/FTP DataCenter Patch Cord Cat.6A (Class EA), LSOH, slim, white, 3 m

Product No.21.44.1703ManufacturerROLINE GREENManufacturer No.21.44.1703

7630049619555



**EAN** (single piece)













Category 6a twisted-pair patch cable with shielded RJ-45 connectors on both sides. Particularly thin and flexible cable with individual pairs of wires in aluminium-laminated foil for use in confined spaces, such as in data centres.

- Durable thanks to moulded-on kink protection
- Suitable as patch cable in patch panels or as device connection cable and intended for use in the LAN
- Contact assignment: 1:1 according to EIA/TIA568, 8 cores
- Structure: 8 cores stranded wire, pairs shielded with alu-laminated foil

ROLINE GREEN products are marked only with a paper tag and build with halogenfree TPE material, without plastic bags and without plastic cable straps for use in eco-friendly environments.

Technical specifications		
Manufacturer	ROLINE GREEN	
Product group	Twisted Pair Cable	
Product type	FTP Patch Cord	

Colour	white
Length	3 m
Scope of delivery	Cable without plastic bag, only marked with a paper label
Shield type	FTP
Transfer quality	Cat6A / Class EA
Quantity of wires	8
Conductor cross section (AWG)	AWG 32
Conductor type	Stranded
Crossed	no
Slim cable	yes
Locking lever	yes
Anti-kink sleeve	Moulded-on
Colour (Spout)	white
Cable LSOH	yes
Material (external cable mantle)	LSOH-TPE
Side 1 Connector Type	RJ-45
Side 1 Connector Gender	Male
Side 2 Connector Type	RJ-45
Side 2 Connector Gender	Male
Connector Type RJ45	Standard
Operating temperature min.	-10 °C
Operating temperature max.	60 °C
Storage temperature min.	-20 °C
Storage temperature max.	75 °C

Weight	51.9 g
Height of packaging (single piece)	10 mm
Width of packaging (single piece)	150 mm
Depth of packaging (single piece)	150 mm
Package weight (single piece)	0.04 kg