
ROLINE GREEN U/FTP DataCenter Patch Cord Cat.6A (Class EA), LSOH, slim, yellow, 0.5 m

Product No. 21.44.3322 roling
Manufacturer ROLINE GREEN

Manufacturer No. 21.44.3322

EAN (single piece) 7630049624429















Category 6a twisted-pair patch cable with shielded RJ-45 connectors on both sides. Particularly thin and flexible cable with individual pairs of wires in aluminium-laminated foil for use in confined spaces, such as in data centres.

- Durable thanks to moulded-on kink protection
- Suitable as patch cable in patch panels or as device connection cable and intended for use in the LAN
- Contact assignment: 1:1 according to EIA/TIA568, 8 cores
- Structure: 8 cores stranded wire, pairs shielded with alu-laminated foil

ROLINE GREEN products are marked only with a paper tag and build with halogenfree TPE material, without plastic bags and without plastic cable straps for use in eco-friendly environments.

Technical specifications		
Manufacturer	ROLINE GREEN	
Product group	Twisted Pair Cable	
Product type	FTP Patch Cord	

Colour yellow Length 0.5 m Scope of delivery Cable without plastic bag, only marked with a paper label Shield type FTP Transfer quality Cat6A / Class EA Quantity of wires 8 Conductor cross section (AWG) Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) yellow Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Type RJ-45 Operating temperature min. Operating temperature min. Operating temperature max. Chapter Day Stranded Cable LSOH Wale Cable LSOH Wale Cable LSOH Wale Cable LSOH Wale Cable Connector Type RJ-45 Side 2 Connector Type RJ		
Scope of delivery Shield type FTP Transfer quality Cat6A / Class EA Quantity of wires 8 Conductor cross section (AWG) Conductor type Stranded Crossed no Slim cable Locking lever Anti-kink sleeve Moulded-on Colour (Spout) Yes Material (external cable mantle) Side 1 Connector Type Side 2 Connector Gender Side 2 Connector Type Standard Operating temperature min. Operating temperature max. Each / Class EA AWG 32	Colour	yellow
Shield type FTP Transfer quality Cat6A / Class EA Quantity of wires 8 Conductor cross section (AWG) Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) yellow Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Gender Side 2 Connector Gender Connector Type RJ45 Side 2 Connector Type RJ-45 Side 2 Connector Gender Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 3 Connecto	Length	0.5 m
Transfer quality Cat6A / Class EA Quantity of wires 8 Conductor cross section (AWG) Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) yellow Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 3 Connector Type RJ-45 Side 4 Connector Type RJ-45 Side 5 Connector Type RJ-45 Side 7 Connector Type RJ-45 Side 8 Connector Type RJ-45 Side 9 Connector	Scope of delivery	Cable without plastic bag, only marked with a paper label
Quantity of wires 8 Conductor cross section (AWG) Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) yellow Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 1 Connector Gender Side 2 Connector Type RJ-45 Side 2 Connector Male Gender Connector Type RJ45 Side 2 Connector Gender Connector Type RJ45 Side 2 Connector Male Gender Connector Type RJ45 Standard Operating temperature min. Operating temperature max.	Shield type	FTP
Conductor cross section (AWG) Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) yellow Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 3 Connector Type RJ-45 Side 4 Connector Type RJ-45 Side 5 Connect	Transfer quality	Cat6A / Class EA
Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) yellow Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 1 Connector Type RJ-45 Side 2 Connector Male Gender Connector Type RJ-45 Standard Operating temperature min. Operating temperature min.	Quantity of wires	8
Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) yellow Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Type RJ-45 Operating temperature min. Operating temperature max.		AWG 32
Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) yellow Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 3 Connector Type RJ-45 Side 4 Connector Type RJ-45 Side 5 Connector Type RJ-45 Side 6 Connector Type RJ-45 Side 7 Connector Type RJ-45 Side 8 Connector Type RJ-45 Side 9 Connector Type RJ-45	Conductor type	Stranded
Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) yellow Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 1 Connector Gender Side 2 Connector Type RJ-45 Side 2 Connector Male Gender Connector Type RJ45 Standard Operating temperature min. Operating temperature max.	Crossed	no
Anti-kink sleeve Moulded-on Colour (Spout) yellow Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 1 Connector Gender Side 2 Connector Type RJ-45 Side 2 Connector Male Gender Connector Type RJ-45 Side 3 Connector Type RJ-45 Side 4 Connector Type RJ-45 Side 5 Connector Type RJ-45 Side 6 Connector Type RJ-45 Side 7 Connector Type RJ-45 Side 8 Connector Type RJ-45 Side 9 Connector Type RJ-45 Side 9 Connector Type RJ-45 Standard Operating temperature and content of the standard of the stand	Slim cable	yes
Colour (Spout) yellow Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 1 Connector Gender Side 2 Connector Type RJ-45 Side 2 Connector Male Gender Connector Type RJ45 Standard Operating temperature min. Operating temperature max.	Locking lever	yes
Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 1 Connector Gender Side 2 Connector Type RJ-45 Side 2 Connector Male Gender Connector Type RJ45 Standard Operating temperature min. Operating temperature max.	Anti-kink sleeve	Moulded-on
Material (external cable mantle) Side 1 Connector Type RJ-45 Side 1 Connector Male Gender Side 2 Connector Type RJ-45 Side 2 Connector Male Gender Connector Type RJ45 Standard Operating temperature min. Operating temperature max.	Colour (Spout)	yellow
mantle) Side 1 Connector Type RJ-45 Side 1 Connector Male Gender Side 2 Connector Type RJ-45 Side 2 Connector Male Gender Connector Type RJ45 Standard Operating temperature of connector Type RJ45	Cable LSOH	yes
Side 1 Connector Gender Side 2 Connector Type RJ-45 Side 2 Connector Gender Connector Type RJ45 Standard Operating temperature min. Operating temperature foo °C max.		LSOH-TPE
Gender Side 2 Connector Type RJ-45 Side 2 Connector Male Gender Connector Type RJ45 Standard Operating temperature min. Operating temperature 60 °C max.	Side 1 Connector Type	RJ-45
Side 2 Connector Gender Connector Type RJ45 Operating temperature min. Operating temperature 60 °C max.		Male
Gender Connector Type RJ45 Standard Operating temperature in a control of the c	Side 2 Connector Type	RJ-45
Operating temperature -10 °C min. Operating temperature 60 °C max.		Male
min. Operating temperature 60 °C max.	Connector Type RJ45	Standard
max.		-10 °C
Character to man experience 20 °C		60 °C
min.	Storage temperature min.	-20 °C
Storage temperature 75 °C max.		75 °C

Weight	13.6 g
Height of packaging (single piece)	20 mm
Width of packaging (single piece)	30 mm
Depth of packaging (single piece)	30 mm
Package weight (single piece)	0.016 kg