
## ROLINE GREEN U/FTP DataCenter Patch Cord Cat.6A (Class EA), LSOH, slim, yellow, 3 m

Product No. 21.44.3326 rolling Manufacturer ROLINE GREEN

**EAN (single piece)** 7630049624467



Manufacturer No.



21.44.3326











Category 6a twisted-pair patch cable with shielded RJ-45 connectors on both sides. Particularly thin and flexible cable with individual pairs of wires in aluminium-laminated foil for use in confined spaces, such as in data centres.

- Durable thanks to moulded-on kink protection
- Suitable as patch cable in patch panels or as device connection cable and intended for use in the LAN
- Contact assignment: 1:1 according to EIA/TIA568, 8 cores
- Structure: 8 cores stranded wire, pairs shielded with alu-laminated foil

ROLINE GREEN products are marked only with a paper tag and build with halogenfree TPE material, without plastic bags and without plastic cable straps for use in eco-friendly environments.

Technical specifications		
Manufacturer	ROLINE GREEN	
Product group	Twisted Pair Cable	
Product type	FTP Patch Cord	

Colour yellow Length 3 m Scope of delivery Cable without plastic bag, only marked with a paper label Shield type FTP Transfer quality Cat6A / Class EA Quantity of wires 8 Conductor cross section (AWG) Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) yellow Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 1 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 2 Connector Type RJ-5 S		
Scope of delivery  Shield type  FTP  Transfer quality  Cat6A / Class EA  Quantity of wires  8  Conductor cross section (AWG)  Conductor type  Stranded  Crossed  no  Slim cable  Locking lever  Anti-kink sleeve  Moulded-on  Colour (Spout)  Cable LSOH  yes  Material (external cable mantle)  Side 1 Connector Type  Side 2 Connector Gender  Connector Type RJ-45  Side 2 Connector Gender  Connector Type RJ45  Standard  Operating temperature min.  Operating temperature max.	Colour	yellow
Shield type FTP Transfer quality Cat6A / Class EA Quantity of wires 8 Conductor cross section (AWG) Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) yellow Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Gender Side 2 Connector Gender Connector Type RJ45 Side 2 Connector Type RJ-45 Side 2 Connector Gender Connector Type RJ45 Standard Operating temperature min. Operating temperature max.	Length	3 m
Transfer quality Cat6A / Class EA  Quantity of wires 8  Conductor cross section (AWG)  Conductor type Stranded  Crossed no  Slim cable yes  Locking lever yes  Anti-kink sleeve Moulded-on  Colour (Spout) yellow  Cable LSOH yes  Material (external cable mantle)  Side 1 Connector Type RJ-45  Side 2 Connector Type RJ-45  Side 3 Connector	Scope of delivery	Cable without plastic bag, only marked with a paper label
Quantity of wires 8 Conductor cross section (AWG) Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) yellow Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Gender Connector Type RJ45 Side 2 Connector Type RJ45 Side 2 Connector Type RJ45 Side 2 Connector Type RJ-45 Side 2 Connector Male Gender Connector Type RJ-45 Side 3 Connector Male	Shield type	FTP
Conductor cross section (AWG)  Conductor type Stranded  Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) yellow Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Type RJ-45 Operating temperature min.  Operating temperature max.	Transfer quality	Cat6A / Class EA
Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) yellow Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 1 Connector Type RJ-45 Side 2 Connector Male Gender Connector Type RJ-45 Standard Operating temperature min. Operating temperature max.	Quantity of wires	8
Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) yellow Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Type RJ-45 Operating temperature min. Operating temperature max.		AWG 32
Slim cable yes  Locking lever yes  Anti-kink sleeve Moulded-on  Colour (Spout) yellow  Cable LSOH yes  Material (external cable mantle)  Side 1 Connector Type RJ-45  Side 2 Connector Type RJ-45  Side 3 Connector Type RJ-45  Side 4 Connector Type RJ-45  Side 5 Connector Type RJ-45  Side 6 Connector Type RJ-45  Side 7 Connector Type RJ-45  Side 8 Connector Type RJ-45  Side 9 Connector Type RJ-45  Standard  Operating temperature min.  Operating temperature foo °C	Conductor type	Stranded
Locking lever yes  Anti-kink sleeve Moulded-on  Colour (Spout) yellow  Cable LSOH yes  Material (external cable mantle)  Side 1 Connector Type RJ-45  Side 1 Connector Gender  Side 2 Connector Type RJ-45  Side 2 Connector Male  Gender  Connector Type RJ45  Standard  Operating temperature min.  Operating temperature max.	Crossed	no
Anti-kink sleeve Moulded-on  Colour (Spout) yellow  Cable LSOH yes  Material (external cable mantle)  Side 1 Connector Type RJ-45  Side 1 Connector Gender  Side 2 Connector Type RJ-45  Side 2 Connector Male  Gender  Connector Type RJ-45  Side 3 Connector Type RJ-45  Side 4 Connector Type RJ-45  Side 5 Connector Type RJ-45  Side 6 Connector Type RJ-45  Side 7 Connector Type RJ-45  Side 8 Connector Type RJ-45  Side 9 Connector Type RJ-45  Side 9 Connector Type RJ-45  Standard  Operating temperature and content of the standard of the stand	Slim cable	yes
Colour (Spout) yellow  Cable LSOH yes  Material (external cable mantle)  Side 1 Connector Type RJ-45  Side 1 Connector Gender  Side 2 Connector Type RJ-45  Side 2 Connector Male  Gender  Connector Type RJ45  Standard  Operating temperature min.  Operating temperature max.	Locking lever	yes
Cable LSOH yes  Material (external cable mantle)  Side 1 Connector Type RJ-45  Side 1 Connector Gender  Side 2 Connector Type RJ-45  Side 2 Connector Male  Gender  Connector Type RJ45  Standard  Operating temperature min.  Operating temperature max.	Anti-kink sleeve	Moulded-on
Material (external cable mantle)  Side 1 Connector Type RJ-45  Side 1 Connector Male  Gender  Side 2 Connector Type RJ-45  Side 2 Connector Male  Gender  Connector Type RJ45 Standard  Operating temperature min.  Operating temperature foo °C  max.	Colour (Spout)	yellow
mantle)  Side 1 Connector Type RJ-45  Side 1 Connector Male Gender  Side 2 Connector Type RJ-45  Side 2 Connector Male Gender  Connector Type RJ45 Standard  Operating temperature of 0 °C min.  Operating temperature max.	Cable LSOH	yes
Side 1 Connector Gender  Side 2 Connector Type RJ-45  Side 2 Connector Gender  Connector Type RJ45  Standard  Operating temperature min.  Operating temperature max.		LSOH-TPE
Gender  Side 2 Connector Type RJ-45  Side 2 Connector Male Gender  Connector Type RJ45 Standard  Operating temperature min.  Operating temperature 60 °C  max.	Side 1 Connector Type	RJ-45
Side 2 Connector Gender  Connector Type RJ45  Operating temperature min.  Operating temperature 60 °C  max.		Male
Gender  Connector Type RJ45 Standard  Operating temperature in a control of the c	Side 2 Connector Type	RJ-45
Operating temperature -10 °C min.  Operating temperature 60 °C max.		Male
min.  Operating temperature 60 °C  max.	Connector Type RJ45	Standard
max.		-10 °C
Storage temperature -20 °C		60 °C
min.	Storage temperature min.	-20 °C
Storage temperature 75 °C max.		75 °C

Weight	48.2 g
Height of packaging (single piece)	20 mm
Width of packaging (single piece)	100 mm
Depth of packaging (single piece)	100 mm
Package weight (single piece)	0.056 kg