## ROLINE GREEN U/FTP DataCenter Patch Cord Cat.6A (Class EA), LSOH, slim, black, 1.5 m


Product No. 21.44.3354

Manufacturer ROLINE GREEN

Manufacturer No. 21.44.3354

**EAN (single piece)** 7630049623675















Category 6a twisted-pair patch cable with shielded RJ-45 connectors on both sides. Particularly thin and flexible cable with individual pairs of wires in aluminium-laminated foil for use in confined spaces, such as in data centres.

- Durable thanks to moulded-on kink protection
- Suitable as patch cable in patch panels or as device connection cable and intended for use in the LAN
- Contact assignment: 1:1 according to EIA/TIA568, 8 cores
- Structure: 8 cores stranded wire, pairs shielded with alu-laminated foil

ROLINE GREEN products are marked only with a paper tag and build with halogenfree TPE material, without plastic bags and without plastic cable straps for use in eco-friendly environments.

Technical specifications		
Manufacturer	ROLINE GREEN	
Product group	Twisted Pair Cable	
Product type	FTP Patch Cord	

ColourblackLength1.5 mScope of deliveryCable without plastic bag, only marked with a paper labelShield typeFTPTransfer qualityCat6A / Class EAQuantity of wires8Conductor cross section (AWG)AWG 32Conductor typeStrandedCrossednoSlim cableyesLocking leveryesAnti-kink sleeveMoulded-onColour (Spout)blackCable LSOHyesMaterial (external cable mantle)LSOH-TPESide 1 Connector TypeRJ-45Side 1 Connector GenderMaleSide 2 Connector TypeRJ-45Side 2 Connector Type RJ45StandardOperating temperature-10 °C	
Scope of delivery Shield type FTP Transfer quality Cat6A / Class EA Quantity of wires 8 Conductor cross section (AWG) Conductor type Stranded Crossed no Slim cable yes Locking lever Anti-kink sleeve Moulded-on Colour (Spout) black Cable LSOH yes Material (external cable mantle) Side 1 Connector Type Side 2 Connector Gender Connector Type RJ45 Side 2 Connector Type RJ45 Side 2 Connector Type RJ45 Side 2 Connector Type RJ45 Standard	
Shield type FTP Transfer quality Cat6A / Class EA Quantity of wires 8 Conductor cross section (AWG) Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) black Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 2 Connector Gender Connector Type RJ45 Standard	
Transfer quality  Quantity of wires  8  Conductor cross section (AWG)  Conductor type  Stranded  Crossed  no  Slim cable  Locking lever  yes  Anti-kink sleeve  Moulded-on  Colour (Spout)  black  Cable LSOH  yes  Material (external cable mantle)  Side 1 Connector Type  Side 2 Connector Type  RJ-45  Side 2 Connector Gender  Connector Type RJ45  Standard	1
Quantity of wires 8 Conductor cross section (AWG) Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) black Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 2 Connector Gender Connector Type RJ45 Standard	
Conductor cross section (AWG)  Conductor type Stranded  Crossed no Slim cable yes  Locking lever yes  Anti-kink sleeve Moulded-on  Colour (Spout) black  Cable LSOH yes  Material (external cable mantle)  Side 1 Connector Type RJ-45  Side 2 Connector Type RJ-45  Side 2 Connector Gender  Connector Type RJ45  Standard	
Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) black Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 2 Connector Gender Connector Type RJ45 Standard	
Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) black Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 2 Connector Gender Connector Type RJ45 Standard	
Slim cable yes  Locking lever yes  Anti-kink sleeve Moulded-on  Colour (Spout) black  Cable LSOH yes  Material (external cable mantle)  Side 1 Connector Type RJ-45  Side 2 Connector Type RJ-45  Side 2 Connector Gender  Side 2 Connector Gender  Connector Type RJ45  Standard	
Locking lever yes  Anti-kink sleeve Moulded-on  Colour (Spout) black  Cable LSOH yes  Material (external cable mantle)  Side 1 Connector Type RJ-45  Side 1 Connector Male  Gender  Side 2 Connector Type RJ-45  Side 2 Connector Type RJ-45  Connector Type RJ-45  Side 3 Connector Type RJ-45  Side 4 Connector Type RJ-45  Side 5 Connector Type RJ-45  Side 6 Connector Type RJ-45  Side 7 Connector Type RJ-45  Side 8 Connector Type RJ-45  Side 9 Connector Type RJ-45  Side 9 Connector Type RJ-45  Side 9 Connector Type RJ-45	
Anti-kink sleeve Moulded-on  Colour (Spout) black  Cable LSOH yes  Material (external cable mantle)  Side 1 Connector Type RJ-45  Side 1 Connector Gender  Side 2 Connector Type RJ-45  Side 2 Connector Male  Gender  Connector Type RJ45  Standard	
Colour (Spout) black  Cable LSOH yes  Material (external cable mantle)  Side 1 Connector Type RJ-45  Side 1 Connector Male  Gender  Side 2 Connector Type RJ-45  Side 2 Connector Male  Gender  Connector Type RJ45  Standard	
Cable LSOH yes  Material (external cable mantle)  Side 1 Connector Type RJ-45  Side 1 Connector Gender  Side 2 Connector Type RJ-45  Side 2 Connector Gender  Connector Type RJ45  Standard	
Material (external cable mantle)  Side 1 Connector Type RJ-45  Side 1 Connector Male  Gender  Side 2 Connector Type RJ-45  Side 2 Connector Male  Gender  Connector Type RJ45  Standard	
Side 1 Connector Type RJ-45  Side 1 Connector Male Gender  Side 2 Connector Type RJ-45  Side 2 Connector Male Gender  Connector Type RJ45  Standard	
Side 1 Connector Gender  Side 2 Connector Type  Side 2 Connector  Male  Side 2 Connector  Male  Gender  Connector Type RJ45  Standard	
Gender Side 2 Connector Type RJ-45 Side 2 Connector Male Gender Connector Type RJ45 Standard	
Side 2 Connector Male Gender  Connector Type RJ45 Standard	
Gender Connector Type RJ45 Standard	
Operating temperature -10 °C	
min.	
Operating temperature 60 °C max.	
Storage temperature -20 °C min.	
Storage temperature 75 °C max.	

Weight	28.4 g
Height of packaging (single piece)	20 mm
Width of packaging (single piece)	100 mm
Depth of packaging (single piece)	100 mm
Package weight (single piece)	0.03 kg