## ROLINE GREEN UTP Data Center Patch Cord Cat.6A (Class EA), LSOH, Slim, grey, 0.3 m

Product No. 21.44.3901


Manufacturer ROLINE GREEN

Manufacturer No. 21.44.3901

7630049623743



**EAN** (single piece)













Category 6A twisted-pair patch cable with RJ-45 connectors on both sides. Particularly thin and flexible cable with individual pairs of wires for use in confined spaces, such as in data centres.

- Durable thanks to moulded-on kink protection
- Suitable as patch cable in patch panels or as device connection cable and intended for use in the LAN
- Contact assignment: 1:1 according to EIA/TIA568, 8 cores
- Structure: 8 cores stranded wire

ROLINE GREEN products are marked only with a paper tag and build with halogenfree TPE material, without plastic bags and without plastic cable straps for use in eco-friendly environments.

Technical specifications			
Manufacturer	ROLINE GREEN		
Product group	Twisted Pair Cable		
Product type	UTP Patch Cables		

Colour grey Length 0.3 m Scope of delivery Cable without plastic bag, only marked with a paper label Shield type UTP Transfer quality Cat6A / Class EA Quantity of wires 8 Conductor cross section (AWG) Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) grey Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Type RJ-5 Side 2 Connector Type RJ-6 Connector Type RJ-5 Side 2 Connector Type RJ-6 Side 2 Connector Type RJ-70 °C Storage temperature max. Storage temperature -20 °C		
Scope of delivery  Shield type  UTP  Transfer quality  Cat6A / Class EA  Quantity of wires  8  Conductor cross section (AWG)  Conductor type  Stranded  Crossed  no  Slim cable  Locking lever  Anti-kink sleeve  Moulded-on  Colour (Spout)  Grey  Cable LSOH  yes  Material (external cable mantle)  Side 1 Connector Type  Side 2 Connector Gender  Connector Type RJ-45  Side 2 Connector Gender  Connector Type RJ45  Standard  Operating temperature min.  Operating temperature max.	Colour	grey
Shield type UTP Transfer quality Cat6A / Class EA Quantity of wires 8 Conductor cross section (AWG) Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) grey Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Gender Side 2 Connector Gender Connector Type RJ45 Side 2 Connector Type RJ-45 Side 2 Connector Gender Connector Type RJ45 Standard Operating temperature min. Operating temperature max.	Length	0.3 m
Transfer quality Cat6A / Class EA  Quantity of wires 8  Conductor cross section (AWG)  Conductor type Stranded  Crossed no  Slim cable yes  Locking lever yes  Anti-kink sleeve Moulded-on  Colour (Spout) grey  Cable LSOH yes  Material (external cable mantle)  Side 1 Connector Type RJ-45  Side 2 Connector Male  Gender  Connector Type RJ-5  Standard  Operating temperature nin.  Operating temperature min.	Scope of delivery	Cable without plastic bag, only marked with a paper label
Quantity of wires 8 Conductor cross section (AWG) Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) grey Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Gender Connector Type RJ45 Side 2 Connector Type RJ45 Side 2 Connector Type RJ45 Side 2 Connector Type RJ-45 Side 2 Connector Male Gender Connector Type RJ-45 Side 3 Connector Male	Shield type	UTP
Conductor cross section (AWG)  Conductor type Stranded  Crossed no  Slim cable yes  Locking lever yes  Anti-kink sleeve Moulded-on  Colour (Spout) grey  Cable LSOH yes  Material (external cable mantle)  Side 1 Connector Type RJ-45  Side 2 Connector Male  Gender  Connector Type RJ-45  Operating temperature min.	Transfer quality	Cat6A / Class EA
Conductor type Stranded Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) grey Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 1 Connector Type RJ-45 Side 2 Connector Male Gender Connector Type RJ-45 Standard Operating temperature and of C	Quantity of wires	8
Crossed no Slim cable yes Locking lever yes Anti-kink sleeve Moulded-on Colour (Spout) grey Cable LSOH yes Material (external cable mantle) Side 1 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 2 Connector Type RJ-45 Side 2 Connector Type RJ-45 Operating temperature min. Operating temperature max.		AWG 32
Slim cable yes  Locking lever yes  Anti-kink sleeve Moulded-on  Colour (Spout) grey  Cable LSOH yes  Material (external cable mantle)  Side 1 Connector Type RJ-45  Side 2 Connector Type RJ-45  Side 3 Connector Type RJ-45  Side 4 Connector Type RJ-45  Side 5 Connector Type RJ-45  Side 6 Connector Type RJ-45  Side 7 Connector Type RJ-45  Side 8 Connector Type RJ-45  Side 9 Connector Type RJ-45  Standard  Operating temperature min.  Operating temperature foo °C	Conductor type	Stranded
Locking lever yes  Anti-kink sleeve Moulded-on  Colour (Spout) grey  Cable LSOH yes  Material (external cable mantle)  Side 1 Connector Type RJ-45  Side 1 Connector Gender  Side 2 Connector Type RJ-45  Side 2 Connector Male  Gender  Connector Type RJ45  Standard  Operating temperature min.  Operating temperature max.	Crossed	no
Anti-kink sleeve Moulded-on  Colour (Spout) grey  Cable LSOH yes  Material (external cable mantle)  Side 1 Connector Type RJ-45  Side 1 Connector Gender  Side 2 Connector Type RJ-45  Side 2 Connector Male  Gender  Connector Type RJ-45  Side 3 Connector Type RJ-45  Side 4 Connector Type RJ-45  Side 5 Connector Type RJ-45  Side 6 Connector Type RJ-45  Side 7 Connector Type RJ-45  Side 8 Connector Type RJ-45  Side 9 Connector Type RJ-45  Side 9 Connector Type RJ-45  Standard  Operating temperature min.  Operating temperature max.	Slim cable	yes
Colour (Spout) grey  Cable LSOH yes  Material (external cable mantle)  Side 1 Connector Type RJ-45  Side 1 Connector Gender  Side 2 Connector Type RJ-45  Side 2 Connector Male  Gender  Connector Type RJ45  Standard  Operating temperature min.  Operating temperature max.	Locking lever	yes
Cable LSOH yes  Material (external cable mantle)  Side 1 Connector Type RJ-45  Side 1 Connector Gender  Side 2 Connector Type RJ-45  Side 2 Connector Male  Gender  Connector Type RJ45  Standard  Operating temperature min.  Operating temperature max.	Anti-kink sleeve	Moulded-on
Material (external cable mantle)  Side 1 Connector Type RJ-45  Side 1 Connector Male  Gender  Side 2 Connector Type RJ-45  Side 2 Connector Male  Gender  Connector Type RJ45  Standard  Operating temperature min.  Operating temperature foo °C  max.	Colour (Spout)	grey
Side 1 Connector Type RJ-45  Side 1 Connector Male Gender  Side 2 Connector Type RJ-45  Side 2 Connector Male Gender  Connector Type RJ45  Standard  Operating temperature of 0 °C max.	Cable LSOH	yes
Side 1 Connector Gender  Side 2 Connector Type RJ-45  Side 2 Connector Gender  Connector Type RJ45  Standard  Operating temperature min.  Operating temperature foo °C  max.		LSOH-TPE
Gender  Side 2 Connector Type RJ-45  Side 2 Connector Male Gender  Connector Type RJ45 Standard  Operating temperature min.  Operating temperature 60 °C  max.	Side 1 Connector Type	RJ-45
Side 2 Connector Gender  Connector Type RJ45  Operating temperature min.  Operating temperature 60 °C  max.		Male
Gender  Connector Type RJ45 Standard  Operating temperature -10 °C min.  Operating temperature 60 °C max.	Side 2 Connector Type	RJ-45
Operating temperature -10 °C min.  Operating temperature 60 °C max.		Male
min.  Operating temperature 60 °C  max.	Connector Type RJ45	Standard
max.		-10 °C
Storage temperature -20 °C		60 °C
min.	Storage temperature min.	-20 °C
Storage temperature 75 °C max.		75 °C

Weight	9.9 g
Height of packaging (single piece)	10 mm
Width of packaging (single piece)	50 mm
Depth of packaging (single piece)	50 mm
Package weight (single piece)	0.01 kg