## ROLINE RM UTP Patch Cord Cat.6A, grey, 0.5 m

**Product No.** 21.45.3100

NE DECYCLED MATERIAL


Manufacturer ROLINE RECYCLED MATERIAL

Manufacturer No. 21.45.3100

**EAN (single piece)** 7630049630406







roline,





Unshielded, pre-assembled category 6A network cable with RJ-45 plugs at both ends. The patch cable from our ROLINE Recycled Material product line is suitable as a patch cable in patch panels or as a device connection cable and is intended for use in local networks.

- Patch cable for networking connections between devices
- Prepared unshielded Twisted Pair cable with RJ-45 connectors on both ends
- Durable due to moulded kink protection
- Flexible cable, suitable for narrow bending
- High quality plugs with gold plated contacts
- Contact settings 1:1, in accordance with the EIA/TIA 568 standard
- Construction: 4-pair stranded copper wire

ROLINE RECYCLED MATERIAL products consist of more than 50% recycled materials. The packaging is even made from 100% recycled material.

Technical specifications		
Manufacturer	ROLINE RECYCLED MATERIAL	
Product group	Twisted Pair Cable	
Product type	UTP Patch Cables	

Length 0.  Shield type U  Transfer quality Ca  Component-Level ye certified  Quantity of wires 8  Conductor cross section (AWG)  Conductor type St  Crossed no  Locking lever ye  Anti-kink sleeve M	D.5 m  UTP  Cat6A / Class EA  yes  AWG 26  Stranded
Shield type  Transfer quality  Component-Level certified  Quantity of wires  Conductor cross section (AWG)  Conductor type  St  Crossed  Locking lever  Anti-kink sleeve  M	Cat6A / Class EA  yes  AWG 26  Stranded
Transfer quality  Component-Level certified  Quantity of wires  Conductor cross section (AWG)  Conductor type  St  Crossed  Locking lever  Anti-kink sleeve  Medical Component-Level Medical Component	Cat6A / Class EA  yes  AWG 26  Stranded
Component-Level yesterified  Quantity of wires 8  Conductor cross section (AWG)  Conductor type Sterified  Crossed not be a section of the conductor of the conductor of type of	yes  B  AWG 26  Stranded
Conductor cross section (AWG)  Conductor type St Crossed no Locking lever ye Anti-kink sleeve M	AWG 26 Stranded
Conductor cross section (AWG)  Conductor type St  Crossed no  Locking lever ye  Anti-kink sleeve M	AWG 26 Stranded
(AWG)  Conductor type St  Crossed no  Locking lever ye  Anti-kink sleeve M	Stranded
Crossed no Locking lever ye Anti-kink sleeve M	
Locking lever ye  Anti-kink sleeve M	าด
Anti-kink sleeve M	
	yes
Colour (Spout) gr	Moulded-on
	grey
Side 1 Connector Type RJ	RJ-45
Side 1 Connector M Gender	Male
Side 2 Connector Type RJ	RJ-45
Side 2 Connector M Gender	Male
Connector Type RJ45 St	Standard
Operating temperature -2 min.	-20 °C
Operating temperature 75 max.	75 °C
Storage temperature -2 min.	-20 °C
Storage temperature 80 max.	30 °C
Weight 20	
Height of packaging 20 (single piece)	20.1 g

Width of packaging (single piece)	70 mm
Depth of packaging (single piece)	70 mm
Package weight (single piece)	0.027 kg