ROLINE RM UTP Patch Cord Cat.6A, white, 20 m

Product No. 21.45.3169

recycled material


Manufacturer ROLINE RECYCLED MATERIAL

Manufacturer No. 21.45.3169

EAN (single piece) 7630049631151







roline





Unshielded, pre-assembled category 6A network cable with RJ-45 plugs at both ends. The patch cable from our ROLINE Recycled Material product line is suitable as a patch cable in patch panels or as a device connection cable and is intended for use in local networks.

- Patch cable for networking connections between devices
- Prepared unshielded Twisted Pair cable with RJ-45 connectors on both ends
- Durable due to moulded kink protection
- Flexible cable, suitable for narrow bending
- High quality plugs with gold plated contacts
- Contact settings 1:1, in accordance with the EIA/TIA 568 standard
- Construction: 4-pair stranded copper wire

ROLINE RECYCLED MATERIAL products consist of more than 50% recycled materials. The packaging is even made from 100% recycled material.

| Technical specifications | | | |
|--------------------------|--------------------------|--|--|
| Manufacturer | ROLINE RECYCLED MATERIAL | | |
| Product group | Twisted Pair Cable | | |
| Product type | U/UTP patch cord | | |

| Colour | white |
|------------------------------------|------------------|
| Length | 20 m |
| Shield type | U/UTP |
| Transfer quality | Cat6A / Class EA |
| Component-Level certified | yes |
| Quantity of wires | 8 |
| Conductor cross section (AWG) | AWG 26 |
| Conductor type | Stranded |
| Crossed | no |
| Locking lever | yes |
| Anti-kink sleeve | Moulded-on |
| Colour (Spout) | white |
| Side 1 Connector Type | RJ-45 |
| Side 1 Connector Gender | Male |
| Side 2 Connector Type | RJ-45 |
| Side 2 Connector Gender | Male |
| Connector Type RJ45 | Standard |
| Operating temperature min. | -20 °C |
| Operating temperature max. | 75 °C |
| Storage temperature min. | -20 °C |
| Storage temperature max. | 80 °C |
| Weight | 450 g |
| Height of packaging (single piece) | 50 mm |
| | |

| Width of packaging (single piece) | 150 mm |
|-----------------------------------|--------|
| Depth of packaging (single piece) | 150 mm |
| Package weight (single piece) | 0.5 kg |